

Well Testing – Defender 5500





Defender 5500 Specifications:

- Internal Diameter 48"
- Thickness 4"
- Pressure Rating 5,500 psi
- Weight 13,400 lbs
- Sand Capacity Between Dumps 500 lbs
- Skid Dimensions (L-W-H) 7'-5.2'-7.8'
- Temp Range -40 to 500 (F)
- H2S / NACE Compliant
- 3" Down-comers Included
- 3" Adapters on all Connections
- ASME Sec VIII Div 1 Coded – Manufactured by Sandtinel
- Performance Range Mostly Depends on Water Cut, BFPD, Sand Particle Size and Gas Rate – Ask for a CFD Estimate
- Up to 10,000 BFPD
- Up to 25mmscpd of Gas
- Ask Your Rep for an Estimate of Performance



Defender 5500 Operating Features:

1. Saw-Tooth Dome – Patented Vapor Lock
 - Creates a phase separation of the gas from the liquids in the incoming mixture,
 - The saw-tooth edge cuts the surface tension at the gas interface allowing it to bleed off from the vapor locked region.
 - Removing the gas temporarily creates a vapor lock, slowing down the liquid and sand substantially, allowing for greater separation times which improves overall sand separation and provides for slug mitigation
2. Vortex Breaker – Sand Lock Patent Pending
 - A cross shaped baffle and sloped plate designed to break-up and block vertical re-circulation patterns in the center of the vessel & also promote horizontal circulation around the outside of the sphere
 - Forces sand to collect & drain at the bottom of the vessel
3. Inner Ring & Weir
 - The ring helps to manage the interface level of the liquid/gas by controlling how the condensate or oil needs to build up before it is able to leave the vessel
 - Inner weir has multiple orthogonal and directionally changing plates for a last line of defense against production of sand



You Require. We Respond.

Greene's Energy Group, a completions and production-focused business servicing exploration and production companies, is ready to help with your next project in the Permian Basin, South Texas and other serviceable locations.

Greene's Energy Group values experience, knowledge, responsiveness and attention to safety as the keys to being a successful oil and gas service company.

Discover Greene's Energy Group at www.greenesenergy.com:

www.greenesenergy.com



For more information, please contact:

CORPORATE HEADQUARTERS

11757 Katy Freeway, Suite 700
Houston, TX 77079
Phone: 281-598-6830
Fax: 281-598-6868

WELL TESTING & FLOWBACK

2211 Industrial Boulevard
Alice, TX
361-664-1515

129 Ranch Road 6096-B
Laredo, TX
956-753-6565

10806 West County Road 74
Midland, TX
432-563-3345

6703 FM 1784
Pleasanton, TX
830-569-1921